## LANDLORD CHECKLIST

## Responsibilities of owners and occupants

☐ Clean ☐ Rubbis approv ☐ All scre good c	cumulations of trash, garbage and junk and sanitary conditions in the dwelling sh should be disposed of in an yed container eens and storm doors should be in condition of insects, rodents or other pests		Plumbing fixtures must be clean and sanitary Outside flowerbeds and yards must be mowed and free of weeds Swimming pools and hot tubs shall be maintained. There are fencing and gate requirements.
Basic eq	uipment and facilities		
	Kitchen sink in good working condition All bathroom fixtures in good working condition water lines) Water heater must be safe and provide a tem Fahrenheit. Egress exits are to be safe and kept maintain	pe	
Light, ventilation and heating			
	providing adequate light  Every habitable room shall have an operable window or other approved method of providing adequate ventilation  Every bathroom shall have an operable window or mechanical ventilation  Every habitable room shall have two wall type outlets or one outlet and a light fixture  Every bathroom, laundry room, furnace room and public hall must have one light fixture		
	Provide clearance between ignition sources, such as light fixtures, heaters and flame producing devices, and combustible materials  All the circuits in the electrical panels must be labeled to ensure they are properly identified Repair or replace damaged or exposed electrical wiring  Provide approved junction boxed for electrical connections in accordance with Electrical Code		
	and install covers for all open junction boxes.  Remove extension cords that are being used as a substitute for permanent wiring  Electrical cords shall not pass through walls, ceilings, doorways or other locations where the cords are subjected to damage. Power taps must be connected directly to an outlet.		
	All outlets and fixtures shall be connected to a source of power maintained in a safe working condition  Additional outlets may be required when multiple adapters are plugged into outlets or		
	extension cords are in use  Heating facilities shall be properly installed and maintain at least 68 degrees (three feet above the floor level)		

## ☐ Provide approved address number that is plainly visible from the street ☐ Every foundation, floor, wall, ceiling and roof shall be reasonably weather tight ☐ All exterior wood or other material which is susceptible to deterioration by the action of the weather must be protected by paint ☐ All interior walls and the ceiling finish must be in good condition ☐ Every inside and outside stair including porches shall be kept in sound condition and good repair ☐ Every plumbing fixture and water and sewer pipe shall be properly installed and maintained in good sanitary working condition, free from defects, leaks and obstructions ☐ Bathroom and kitchen floors shall be structurally sound and kept in a clean and sanitary condition ☐ All equipment and utilities shall be maintained in satisfactory working order ☐ Remove all combustible storage from attic, under-floor and concealed spaced –OR- provide one-hour fire resistive construction on the storage side of such areas -OR- provide sprinkler protection ☐ Remove and discontinue to the storage or combustible materials in all electrical distribution equipment rooms. ☐ Discontinue the storage of gas-fuel equipment (lawn maintenance, snow removal, etc.) inside buildings -OR- store only in rooms specifically designed and separated from other portions of the building Space, use and location requirements ☐ Every dwelling unit shall contain at least 120 square feet of floor space ☐ Every sleeping unit shall contain at least 70 square feet of floor space ☐ Every habitable room shall have a required ceiling height of seven feet **Smoke Detectors** ☐ Homes built after March 20<sup>th</sup>, 1995 are required to have a smoke detector in each bedroom or sleeping room ☐ Smoke detector outside each separate sleeping area are required in all dwellings ☐ Unless otherwise recommended by the manufacturer, single – and multiple-station smoke alarms installed in one- and two-family dwellings shall be replaced when they fail to respond to operability tests, but shall not remain in service longer than 10 years from the date of manufacture. **Egress** ☐ Remove unapproved locking devices from exit doors. Exit doors shall be openable from the inside without the use of a key or any special knowledge or effort ☐ Remove and discontinue the storage of combustible materials in exits and exit enclosures.

Maintenance of parts of dwelling and dwelling units